

Index

- Acceleration
 - initial heading error, 198
 - longitudinal, 317
 - maneuver, 6, 208
 - maneuvering target, 197
 - ramjet, 202
 - rocket, 204
 - turbojet, 202
- Acquisition, 3, 380, 447, 449
- Actuator, 190
- Advanced concept technology
 - demonstration, 380, 433, 447
- Aerodynamic heating, 42–43, 162
- Aerodynamic center, 40, 47, 363, 443
- Aeroelasticity, 299
- Aircraft integration, 298, 314
- Airframe, 112
- Air loads, 178–179
- Air-to-air missile, 7, 313, 394, 404
- Air-to-surface missile, 8
- Air turbo rocket, 90–91
- Altitude, 1, 11, 213, 222, 278, 336, 346
- Aluminum, 134, 136, 227, 319, 437
- Ammonium perchlorate, 122, 276, 437
- Angular resolution, 27, 225
- Annular inlet, 110–111
- Antenna, 11, 24, 240, 396, 439
- Advanced Strategic Air Launched
 - Missile (ASALM), 15, 71, 338
- Antiradiation homing (ARH), 242–243
- Aspect ratio, 53, 60, 69, 185, 305, 437
- Atmosphere, 236–237, 346, 447
- Atmospheric attenuation, 25
- Axial force, 202, 342, 344, 438
- Axial load, 356

- Bandwidth, 27–28, 39, 225, 272, 396, 429
- Bank-to-turn, 54, 69, 339, 447
- Base area, 32, 34
- Base drag (base pressure), 31–32

- Baseline missile, 6, 14, 23, 28, 40, 122, 181, 192, 209
- Battery, 24, 190–191, 396
- Battle damage indication (BDI), 11, 225, 289, 396
- Beam range, 199
- Beamwidth, 25, 417
- Bending moment, 180
- Binder, 120, 133
- Blast, 21, 57
- Blast tube, 136–137
- Blunt nose, 33, 171
- Boattail drag, 34
- Body bending frequency, 28, 414
- Body
 - aerodynamic center, 40, 47, 53
 - bending, 4, 28
 - center of pressure, 53
 - drag coefficient, 31–32
 - normal force, 36
 - weight, 16, 69, 100, 141
- Boost, 125, 127, 129, 151, 214, 319
- Boost-glide trajectory, 1
- Booster, 105, 108, 235, 346
- Boresight, 13, 197
- Boundary layer, 47, 163
- Breguet range equation, 84–85, 202–203
- Buckling, 177, 356
- Burn area, 122
- Burn rate, 127

- Canard, 44–49
- Canister launch system (CLS), 296
- Captive flight, 119, 386
- Capture efficiency, 114–115, 117
- Carbon, 121–122
- Carriage, 274–277
- Case, 134–135
- Casting, 150–151, 153, 157, 429
- Center of gravity, 146–147, 209

- Center of pressure, 40, 53, 65, 76, 438, 443
- Ceramic, 89, 153, 161
- Chamber pressure, 122, 125–127, 137, 176, 357
- Characteristic velocity, 123, 127, 238, 321, 357
- Charge, 246, 248–250, 254, 437–438, 443
- Choked flow, 124
- Circular error probable (CEP), 257, 423
- Climb, 201, 204–205, 209, 330
- Cloud, 219–220
- Clutter, 225, 404
- Coast, 130, 195, 200, 210, 336
- Collision course, 259
- Combustion chamber, 83, 91, 132
- Command, control, communication (C³), 11, 429, 477
- Command, control, communication, computers, intelligence, surveillance, reconnaissance (C4ISR), 11, 429
- Communication, 430, 433
- Composite material, 52, 155, 157, 160
- Composite propellant, 133–134
- Compressed carriage, 17, 235, 304–305
- Compressor, 86–88, 413
- Computational fluid dynamics (CFD), 38, 353, 391
- Computer-aided sizing, 313, 354, 376
- Conceptual design, 4–7, 14–16, 40, 137, 141
- Conductivity, 163, 170
- Configuration buildup, 77–78
- Configuration sizing, 1, 49, 201, 412, 453
- Conical flow, 114
- Conical nose, 114
- Contrast, 13
- Control effectiveness, 56, 61, 201, 209, 392
- Control, axis
 - pitch, 55–56, 69
 - roll, 55–56, 72, 389
 - yaw, 55–56, 69–72, 147, 299
- Control, types of
 - all movable, 55
 - canard, 56–59, 61–62, 193, 375, 396
 - flap, 55
 - lattice, 60–61, 396
 - tail, 56–66
 - unconventional, 43, 57, 66–67
 - wing, 56, 64–65, 263
- Cost
 - development, 3
 - logistics, 11, 141, 284, 291–293
 - production, 284, 286–288, 290, 356, 410
 - system development and demonstration (SDD), 356
- Counter-countermeasures, 240
- Countermeasures, 239, 395
- Cross coupling, 392
- Crossflow, 36, 40
- Cruciform design, 51, 72, 109–111, 317
- Cruise missile, 3, 42, 52, 54, 56, 191
- Cruise trajectory, 356
- Damping characteristics, 393
- Data link, 11, 225, 232–233, 396, 429,
- Degrees of freedom, 199
- Delta wing, 52–53
- Demonstration and validation (Demval), 382
- Density, 161–162, 202, 237, 245, 351, 396
- Design,
 - conceptual, 4–5, 7, 14–15, 40, 74, 76, 141
 - criteria, 76–77, 79, 117, 413–414
 - detailed, 83
 - loads, 149, 176
 - of experiments (DOE), 7, 333, 402, 424
 - preliminary, 7, 78, 200, 353, 381–392
 - validation, 380, 384–385
- Detection range, 23–24, 26, 229–230, 277, 279
- Development,
 - facilities, 386
 - process, 379, 381
 - tests, 386–388
- Diameter considerations, 245
- Dielectric constant, 186
- Diffuser, 16
- Discharge coefficient, 123
- Diving flight trajectory, 215
- Documentation, 15, 408, 433, 454
- Dome
 - bandpass, 186
 - error slope, 29–30, 64, 69, 71, 265, 395
 - faceted, 29–30, 395

- material alternatives, 141
- multilens, 29–30, 395
- stress, 172, 174
- weight, 188–189
- window, 29–31
- Double base propellant, 133–134
- Drag
 - base, 31–32, 34, 50
 - boattail, 34–35
 - components of, 212, 367
 - crossflow, 36, 40, 72, 356
 - definition of, 4, 22
 - skin friction, 31–32, 49–51
 - wave, 31–33, 49–51
- Ducted rocket, 7–8, 71, 83, 97, 121–122
- Dynamic pressure, 2, 22, 48, 203, 207
- Dynamic stability, 393, 410

- Effective navigation ratio, 259–261, 266, 268
- Ejection launch, 300, 303
- Electro-optical, 222, 239
- End burning grain, 127, 129
- Engine nomenclature, 342
- Environment, 13, 150, 224, 307
- Exit, 16, 85, 137
 - pressure, 91, 93
 - velocity, 85–86, 93
- Expansion ratio, 125, 137, 319, 332, 357, 420, 443

- Faceted dome, 29–30
- Factor of safety, 149, 186
- Field of regard, 30, 298
- Field of view, 27, 224
- Fineness ratio, 22, 27–28, 30, 339, 413
- Fire control, 198, 306
- Firepower, 3, 245, 303
- Flap, 55
- Flare, 41–43, 413
- Flight loads, 178–179
- Flight path angle, 122, 201, 259, 330, 337
- Flight performance, 4, 6–7, 141–142, 146
- Flow path geometry, 16, 342
- Flow separation, 31, 50, 392
- Flow types
 - laminar, 163
 - turbulent, 163

- Forebody types
 - conical, 118
 - faceted, 29, 395
 - hemispherical, 33, 184, 188
 - tangent ogive, 28–29, 264
 - window, 29–30, 263, 395
- Four degrees of freedom, 447
- Fragment, 249, 356, 442
- Free-to-roll tails, 54, 58
- Freestream Mach number, 61, 98, 440
- Frequency, 25, 29, 223, 226, 383, 414, 439, 445
- Fuel
 - alternatives, 120, 350
 - density, 85, 120–121, 202
 - heating value, 18, 88, 97
 - observables, 133
- Fuel-to-air ratio, 87–90, 100, 353
- Full expansion nozzle, 124

- Gain, 235, 277
- Gas generator, 97, 122
- Gel motor, 396
- Glide trajectory, 83, 335, 338
- Glint, 270–271
- Global positioning system (GPS), 224
- Grain configuration, 317
- Graphite, 155, 162
- Gravitational constant, 206
- Ground handling loads, 149, 183
- Guidance, 247, 414

- Hardware in loop, 291, 349
- Heading error 198, 232, 266, 414, 444, 484,
 - Heat capacity, 159
 - Heat flux, 172
 - Heat sink, 83, 173
 - Heat transfer, 136, 162–163, 392
 - Heating, aerodynamic, 141, 162, 175, 237, 356
 - Heating value of fuel, 88
 - Hemispherical nose, 33
 - Hinge moment, 48, 193, 392
 - Hoop stress, 183–184, 361
 - Horizontal flight, 122, 213, 215
 - House of quality, 5, 17, 371, 376, 409, 431
 - Hydroxyl-terminated polybutadiene binder (HTPB) 120
 - Hypersonic Mach number, 122, 354
 - Hypersonic missile, 1, 157, 161, 396

- Imaging seeker, 210
- Impulse
 - specific, 16, 18, 72, 81–86, 94–98, 125
 - total, 202, 319
- Induced roll, 62, 64–66
- Inert weight, 144
- Inertia, moment of, 146–149, 201, 319, 439, 451
- Inertial navigation system (INS) 225, 227, 395, 448
- Infrared (IR) seeker, 25
- Initial operational capability (IOC) 13, 431, 448
- Inlet
 - alternatives, 110
 - capture efficiency, 114–115
 - cowl, 109, 112
 - integration, 112, 119, 414
 - spillage, 113
 - start, 116–118
 - throat, 116, 437
- In-line surfaces, 55–56, 391
- Insensitive munition, 133, 388, 488
- Instantaneous field of view (IFOV), 27, 448
- Insulation, 135, 158–160, 396
- Integral rocket-ramjet (IRR), 106, 449
- Integrated product process development (IPPD), 285, 431, 449
- Interdigitated surfaces, 54–56, 391
- Internal carriage, 275, 396
- IR dome, 30, 172
- Isentropic flow, 86, 92, 100, 356

- Jet interaction, 43, 57, 67, 393
- Jet vanes, 66, 68

- Kill probability, 3, 248, 250
- Kinetic energy, 136, 241, 255, 356

- Laminar flow, 163
- Lattice fins, 60–61
- Launcher, 134, 275, 300, 304, 359
- Launch platform integration, 1, 9, 56, 219–311
- Launch range, 313, 356
- Lead angle, 197, 215–216, 356
- Learning curve, 287–288
- Length considerations, 296
- Lessons learned, 399–415
- Lethality, 5, 13, 219
- Lift, 16, 21, 348, 438, 440
- Lifting body, 21, 34–38, 396
- Lift-to-drag ratio, 21, 38, 202
- Limit stress 184, 421
- Linear wing theory, 44–45, 47, 76
- Line of sight, 69–70
- Load factor, 149
- Load distribution, 178, 180
- Loads, 38, 149, 176, 183
- Local angle of attack, 44, 58, 209
- Localized buckling, 134, 154, 178
- Lofted trajectory, 69, 313
- Logistics, 11, 71, 91, 291, 293
- Low observables, 29, 38, 239

- Mach angle, 114, 444
- Maneuverability, 1, 7, 67, 78, 201, 414
- Manufacturing process, 361
- Mass ratio, 249–250
- Material density, 186, 188
- Material strength, 154, 156
- Maximum angle of attack, 179–180, 209, 393
- Maximum effective operating pressure, 149, 184, 449
- Maximum lift coefficient, 34–36
- Maximum range, 84, 199, 368, 441
- Maximum speed, 122
- Mean aerodynamic chord (MAC), 186, 366, 438, 449
- Measures of merit, 10, 13, 186, 190, 219, 334
- Micromachined electromechanical systems (MEMS), 194, 294, 396, 449
- Military standard, 120, 449
- Minimum range, 198–199, 299
- Minimum smoke, 122, 133, 276–277
- Miss distance, 71, 246, 248, 257, 266, 268, 357
- Missiles, types of, 8, 145
- Mission definition, 14, 356
- Mission planning, 278–279
- Mission requirements, 5, 10, 356
- Modulus of elasticity, 28, 154, 439
- Moment of inertia, 146–149, 201, 319
- Monocoque construction, 150
- Motor case
 - chamber pressure, 178
 - heating, 136
 - materials, 134–135
 - weight, 128–129

- Natural frequency, 70–71
 Navigation ratio, 259–260
 Newtonian impact theory, 44–45, 391
 Nitrocellulose, 133–134
 Noise, 229, 271–274
 Nomogram, 180–181
 Normal distribution, 237, 239, 257
 Normal force
 from angle of attack, 36, 46
 from control deflection, 73, 264
 Normal force coefficient
 body, 36, 46, 78
 wing, 45–46
 tail, 46, 363
 total, 46, 363
 Normal force curve slope, 36, 46
 Nose geometry, 32
 Nose fineness, 4, 9, 29, 413, 440
 Nose inlet, 109, 111–112
 Nozzle
 discharge coefficient, 121, 123, 438
 exit area, 32, 126, 437
 exit pressure, 91–95, 98–99
 exit velocity, 83, 85–86, 93–94
 expansion ratio, 123–124, 126, 319, 443
 materials, 68, 136
 throat, 125–126, 137

 Oblique shock, 61, 109, 113, 117, 119–120
 Observables, 38, 121, 133, 239, 274, 276
 Off boresight, 13–14, 198, 323
 One degree of freedom, 261, 447
 Optimum
 climb, 234–235, 356
 cruise, 233–234
 design, 216, 353, 375
 dive, 234–235
 trajectory, 338

 Pareto, 17, 323
 Parts count, 150, 281
 Penetration, 13, 241
 Pintle motor, 85, 396
 Pitching moment, 16, 38–41, 319
 Pitot-static probe, 300
 Planform, 21, 145, 339
 Point load, 180
 Power supply, 1, 190–193
 Precision, 3, 354
 guided munition, 10, 11, 449
 strike accuracy, 3, 231, 414
 strike missile, 3, 10–11, 36, 224, 298
 Preliminary design, 7, 78, 199, 381, 391, 431
 Pressure, 2
 base, 34, 319
 chamber, 122, 125–126, 420, 441
 recovery, 110
 Probability of kill, 248, 250, 441
 Production process, 287–288, 290
 Progressive thrust, 129
 Propellant, 4–7, 128–130, 132–134
 burn area, 126, 137, 437
 cross section, 129
 extruded, 289, 361
 flow rate, 85, 97, 121
 fraction, 81, 123, 203
 grain, 97, 122, 128–130, 281
 minimum smoke, 123, 133, 276
 properties, 133
 reduced smoke, 132–133, 277
 selection, 333
 slotted, 128–129, 420
 web, 129
 Proportional guidance, 259–260, 354, 414
 Pulse motor, 130–131
 Pultrusion, 150–152, 194, 396

 Radar, 3, 8, 23, 186, 222
 beam width, 227, 272
 cross section, 3, 24, 30, 155, 239
 frequency, 186, 239, 449
 range, 23–24, 277
 resolution, 23–25, 224
 Radial burn, 129, 130
 Radiation, 156, 171, 223, 228, 447
 Radome, 28, 166, 187, 189, 263
 Rail launch, 276, 297, 304
 Rain, 186, 188, 222, 386
 Ramjet, 7, 16, 95–112
 engine-booster integration, 81, 105–108
 inlet, 81, 109–112
 length, 7, 97–98, 105
 specific impulse, 16, 81, 83, 97–98, 347, 348
 temperature limit, 100–105, 345
 thrust, 83, 98–100, 356, 389
 Range, 3–19, 313–329, 338–350
 ballistic, 212–213, 368
 climb, 85

- Range (*Continued*)
 coast, 210–211
 cruise, 13, 38, 203
 detection, 5, 23–24, 26, 227, 356
 dive, 205, 235, 356
 launch, 313–314, 316–317, 356
 maximum, 84, 144, 198, 410
 minimum, 197–198, 267, 299, 410
 recognition, 314–315, 441
 sensitivity, 17, 24
 standoff, 13, 240, 277, 297,
 313–329, 376
- Rate of climb, 422
 Rate of dive, 39
 Reaction jet, 43, 57, 69
 Recovery factor, 158, 172, 441
 Recovery temperature, 156, 158
 Rectangular planform, 53
 Reduced smoke, 132–133, 274
 Regressive thrust, 128–129
 Reliability, 122, 281–282
 Risk, 3, 407
 Robustness, 9, 199, 219–241,
 338–350
 Rocket motor, 7, 29, 90, 122–128
 Roll, 72–73
 attitude, 72, 77, 392, 393
 control, 55–56, 58, 284
 orientation, 21, 69, 72–73
 stabilization, 56
 Rolling airframe, 56, 70
 Rolling moment, 54, 56, 200
- Safety, 83, 132, 149–150
 Scramjet, 81, 83, 234, 388, 419, 448
 Seeker, 1, 29–30, 186–190
 Seeker dome, 71, 141, 186–190
 Surface-to-air missile, 9, 68, 242, 389
 Semimonocoque construction, 150
 Sensitivity, 5, 17, 141–142, 347, 410
 Ship integration, 132
 Shipboard launching, 430
 Shock angle, 61, 115
 Shock wave, 31, 50, 112, 340, 414
 Sideslip, angle of, 69, 71, 179, 180, 301
 Signal, 21, 25, 188, 441
 Sizing, 1, 6, 9–10, 74–76, 313–377
 Six degrees of freedom, 200, 291, 447
 Skid-to-turn, 54, 69, 70
 Skin friction drag, 31, 49, 365, 366
 Slender body theory, 36, 76, 356
 Slender wing theory, 45, 356, 375
 Slotted propellant grain, 128
 Smoke, 122, 133, 274
 Solid propellant rocket, 83, 85, 145
 Sound, speed of, 32, 49, 95, 137
 Sparrow missile, 65, 163, 376, 402
 Specific heat, 86–88, 101, 356
 Specific impulse, 16, 83, 94–95, 348
 ducted rocket, 83, 97, 121
 ramjet, 16, 71, 97–98, 347–348
 rocket, 81, 83
 scramjet, 83
 turbojet, 81, 94–95
- Spillage, inlet, 81
 Split canard, 13, 62
 Spreadsheet, 313, 355–356
 Stability, 1, 5, 38–40, 76–77
 static, 21, 38–40, 72–73, 75
 dynamic, 354, 391–393
 neutral, 74, 262, 357
 Stabilizer, 1, 41–43, 319
 Stage, rocket, 90, 145, 192
 Stagnation temperature, 158
 Standard atmosphere, 163, 236, 346
 Standard deviation, 444
 State of the art, 1, 7–9, 393–394, 399
 Static margin, 4, 13, 73, 236
 Steady flight, 204, 207
 Steady-state temperature, 162, 171–172
 Steel, 28, 134, 136
 Stiffeners, 150
 Store, 39, 180, 299
 carriage, 281, 297, 299, 392
 separation, 39, 297, 299, 302
 suspension, 303
 Strength, 53, 150, 152, 154, 382
 Stress, 32, 129, 141, 172–175, 295
 Structure, 1, 28, 52, 149–150,
 158–160
 design, 141, 149, 150, 175–186
 efficiency, 157
 material, 156, 357, 361
 weight, 141, 175, 185
 Submarine integration, 295–296
 Subsystems, 5, 14, 38, 141–142
 Surface planform, 21, 46, 53, 396
 Surface-to-air missile, 9, 68, 293
 Surface-to-surface missile, 9
 Survivability, 9, 11, 243, 277–281
 Sustain flight, 124, 171, 325
 Synthetic aperture radar (SAR),
 224, 395
 Synthesis, 5, 21, 141, 406

- System analysis, 11, 291, 385
- System development and demonstration (SDD), 237, 356, 379, 407, 431
- Tactical Missile Design (TMD)
 - spreadsheet, 355
- Tail, 5, 7, 42, 56
 - arrangement, 60
 - control, 34, 56, 58
 - force, 44, 46
 - sizing, 74–76, 146
- Tangent ogive nose, 264
- Target, 3, 24
 - acquisition, 3, 224, 226, 447
 - aspect, 215, 259, 316
 - damage, 11, 225
 - detection, 24, 224, 229
 - error (TE), 232–233
 - kill, 3, 13, 250
 - location error (TLE), 11, 232
 - maneuver, 6, 259, 414
 - recognition, 3, 224, 395
 - types, 243
- Technology, 1, 21, 86–92, 100–105
 - assessment, 5, 379–380
 - availability date (TAD), 382, 433
 - development, 5, 11, 379, 390–393
 - readiness level (TRL), 379, 381, 431
 - roadmap, 5, 379–380, 410
- Temperature, 18, 86–92
- Tensile stress, 154, 184, 444
- Terminal guidance, 231, 259
- Test, 6, 283, 289–300, 358, 389
- Thermal, 23, 83, 158, 162–172, 287
 - choking, 83, 102–103
 - conductivity, 135, 158–159, 170
 - diffusivity, 159, 165, 443
 - expansion, 131, 172, 174, 186
 - stress, 141, 172–175
- Thermally thick surface, 165, 167
- Thermally thin surface, 162, 164
- Thickness, 28, 47
 - airframe, 163, 177, 182, 356
 - motor case, 178, 357
 - surface, 51, 53, 61, 356
- Thin wall cylinder, 28
- Threat radar, 61, 243, 244
- Three degrees of freedom, 201, 391, 447
- Throat, nozzle, 16, 125–126, 137, 342, 437
- Thrust considerations, 81, 121
- Thrust
 - magnitude control (TMC), 81–85, 130–132
 - ramjet, 83–86, 89, 95–97, 100–105
 - rocket, 7, 81, 121–128
 - turbojet, 81, 86–92, 94–95, 396
- Thrust vector control, 14, 43, 66, 286, 331
- Time to climb, 442
- Time constant, 43, 77, 260–265, 362
- Time critical target, 84, 243
- Titanium, 151–157, 396
- TNT, 247, 252, 255
- Total impulse, 202, 265, 319
- Trajectory
 - ballistic, 197, 212, 266, 337
 - boost-coast, 131, 197
 - boost-sustain-coast, 130–131
 - boost-glide, 83, 217
 - climb, 83, 204–209, 235
 - coast, 197, 210–212, 421
 - cruise, 17, 197, 234, 418, 428
 - dive, 235, 434, 444
 - glide, 83, 205, 217, 286, 337
 - lofted, 69, 313, 338
 - turn, 206–209
- Trapezoidal planform, 53
- Triangular planform, 29
- Tri-tail, 56
- Trim angle of attack, 7, 73, 209, 414
- Trim normal force coefficient, 46
- Turbine, 81, 85, 92, 94, 246, 396
- Turbojet
 - compressor, 81, 83, 86
 - engine, 191
 - material, 89, 90
 - specific impulse, 16, 91–96
 - turbine, 89–90
 - thrust, 56, 419, 442
- Turbo ramjet, 89, 90
- Turbulent flow, 163
- Turn
 - radius, 197, 207–209, 330
 - rate, 207–210, 263, 330
- Two degrees of freedom, 447
- Ultimate strength, 319, 321
- Uncertainty, 63, 150, 184
- Undamped natural frequency, 71
- Underexpanded nozzle, 237
- Uniform load, 180, 185
- Unguided flight trajectory, 39, 354
- Unit cost, 3, 287–288

- Unmanned
 - air vehicle, 11, 26, 141, 245
 - combat air vehicle, 245
- Unpowered flight, 386
- Velocity, 122, 197–199, 452
 - ballistic, 144, 145, 212–214, 450
 - burnout, 143, 214, 327–329
 - climb, 204–205
 - coast, 210–213, 329, 356
 - cruise, 30, 326, 339
 - dive, 205, 235, 257
 - fragment, 21, 248, 252–253
 - sustain, 319, 327, 420, 442
- Vertical launch system (VLS), 135, 296
- Volumetric
 - efficiency, 38, 97, 129, 134–135, 420
 - loading, 96, 121, 129, 183
- Vortices, 54, 65
- Vulnerable area, 250, 251
- Wall temperature, 166, 357
- Warhead
 - blast fragmentation, 248, 250–253, 257, 356
 - kinetic energy, 242, 257
- Wave drag, 31–33, 49–51
- Weather, 25, 219–221, 372
- Weight
 - actuator, 52
 - airframe, 11, 28, 160, 188, 319
 - density, 212, 356, 357
 - dome, 141–144, 320
 - fuel, 81, 84, 425, 439
 - inert, 144, 348–349, 420,
 - insulation, 356, 421
 - motor, 132, 183
 - power supply, 141, 144, 190–193, 356
 - propellant, 121–125, 128, 143, 183, 202, 318, 420
 - reduction, 7, 294
 - statement, 16, 146
 - structure, 1, 141, 179, 185
 - subsystems, 85, 144, 146, 309, 421
 - warhead, 399, 404
- Wetted area, 32, 189, 366
- Wind tunnel test, 38, 163, 178–179, 349, 385, 392
- Window dome, 29–31, 271
- Wing
 - aerodynamic center, 48, 76
 - area, 7, 45, 336
 - arrangement, 54
 - center of pressure, 40, 76
 - characteristics, 243, 251, 372
 - control, 48, 49, 54–56, 64
 - delta, 51–53
 - double delta, 52
 - drag, 438
 - forward swept, 51–52, 65, 79
 - location, 21, 75, 317, 422, 443
 - mean aerodynamic chord (MAC), 47–53, 186, 438
 - normal force, 16, 18, 21, 34–36, 200, 438
 - planform, 21, 38, 44–46
 - rectangular, 53
 - section, 43, 49–51, 317
 - size considerations, 21, 112
 - sizing, 313, 329–331, 335
 - trapezoidal, 51, 53
 - weight, 106, 141, 135
- Wing-body-tail, 78, 391
- Wing theory, 44, 49, 356
 - linear, 44, 76
 - Newtonian, 44–45, 49–50, 356
 - slender, 45, 49, 356
- X tail, 56, 60
- Yawing moment, 73, 77, 200
- Yield strength, 178
- Zero lift drag, 21, 51, 199
 - body, 32
 - tail, 51
 - total, 31, 51
 - wing, 51, 47